Supertex inc.

TD9944

Low Threshold

Preliminary

Dual N-Channel Enhancement-Mode Vertical DMOS FETs

Ordering Information

BV_{DSS} / BV_{DGS}	$R_{DS(ON)}$ (max)	$V_{GS(th)}$ (max)	$I_{D(ON)}$ (min)	Package
				SO-8
240V	6Ω	2.0V	1.0A	TD9944TG

Features

- Dual N-channel devices
- Low threshold — 2.0V max.
- High input impedance
- Low input capacitance — 125 pF max.
- Fast switching speeds
- Low on resistance
- Free from secondary breakdown
- Low input and output leakage

Applications

- Logic level interface – ideal for TTL and CMOS
- Solid state relays
- Battery operated systems
- Photo voltaic drive
- Analog switches
- General purpose line driver
- Telecom switches

Absolute Maximum Ratings

Drain-to-Source Voltage	BV_{DSS}
Drain-to-Gate Voltage	BV_{DGS}
Gate-to-Source Voltage	± 20V
Operating and Storage Temperature	-55°C to +150°C
Soldering Temperature*	300°C

* Distance of 1.6 mm from case for 10 seconds.

Low Threshold DMOS Technology

These dual low threshold enhancement-mode (normally-off) transistors utilize a vertical DMOS structure and Supertex's well-proven silicon-gate manufacturing process. This combination produces devices with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, these devices are free from thermal runaway and thermally induced secondary breakdown.

Supertex vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Pin Configuration



SO-8

5/14/93

Electrical Characteristics (each device, @ 25°C unless otherwise specified)

Symbol	Parameter	Min	Typ	Max	Unit	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	240			V	V_{GS} = 0, I_D = 2mA
$V_{GS(th)}$	Gate Threshold Voltage	0.6		2.0	V	$V_{GS} = V_{DS}$, I_D= 1mA
$\Delta V_{GS(th)}$	Change in $V_{GS(th)}$ with Temperature			-5.0	mV/°C	$V_{GS} = V_{DS}$, I_D= 1mA
I_{GSS}	Gate Body Leakage			100	nA	V_{GS} = ± 20V, V_{DS} = 0V
I_{DSS}	Zero Gate Voltage Drain Current			10	µA	V_{GS} = 0, V_{DS} = Max Rating
				1.0	mA	V_{GS} = 0, V_{DS} = 0.8 Max Rating, T_A = 125°C
$I_{D(ON)}$	ON-State Drain Current	0.5	1.9		A	V_{GS} = 4.5V, V_{DS} = 25V
		1.0	2.8			V_{GS} = 10V, V_{DS} = 25V
$R_{DS(ON)}$	Static Drain-to-Source ON-State Resistance		4.0	6.0	Ω	V_{GS} = 4.5V, I_D = 250mA
			4.0	6.0		V_{GS} = 10V, I_D = 0.5A
$\Delta R_{DS(ON)}$	Change in $R_{DS(ON)}$ with Temperature			1.4	%/°C	V_{GS} = 10V, I_D = 0.5A
G_{FS}	Forward Transconductance	300	600		m℧	V_{DS} = 25V, I_D = 0.5A
C_{ISS}	Input Capacitance		65	125	pF	V_{GS} = 0, V_{DS} = 25V, f = 1 MHz
C_{OSS}	Common Source Output Capacitance		35	70		
C_{RSS}	Reverse Transfer Capacitance		10	25		
$t_{d(ON)}$	Turn-ON Delay Time			10	ns	V_{DD} = 25V, I_D = 1.0A, R_{GEN} = 25Ω
t_r	Rise Time			10		
$t_{d(OFF)}$	Turn-OFF Delay Time			20		
t_f	Fall Time			20		
V_{SD}	Diode Forward Voltage Drop			1.8	V	V_{GS} = 0, I_{SD} = 1.0A
t_{rr}	Reverse Recovery Time		300		ns	V_{GS} = 0, I_{SD} = 1.0A

Notes:
1. All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300µs pulse, 2% duty cycle.)
2. All A.C. parameters sample tested.

Switching Waveforms and Test Circuit





Typical Performance Curves

Output Characteristics



Saturation Characteristics



BV_{DSS} Variation with Temperature



On-Resistance vs. Drain Current



Transfer Characteristics



$V_{(th)}$ and R_{DS} Variation with Temperature



Typical Performance Curves

Capacitance vs. Drain-to-Source Voltage



Gate Drive Dynamic Characteristics



Transconductance vs. Drain Current



Supertex inc.
Leadership in CMOS/DMOS Technologies

1350 Bordeaux Drive, Sunnyvale, CA 94089
TEL: (408) 744-0100 • FAX: (408) 734-5247